



NOTE:
 1. Rating: AC125V 5A/250V 3A
 2. Operating froce: 25±10gf
 3. Mechanical Life: 1,000,000
 3. Electrical Life: 6000-10,000

ITEM	PART NAME	TER.NO.	QTY.	MATERIAL	FINISHING	REMARK
⑧	Shrapnel 2	—	1	Copper Alloy	—	—
⑦	Shrapnel 1	—	1	Beryllium Copper	—	—
⑥	Contact	—	1	Copper Alloy	Plating silver	—
⑤	Lever	—	1	Copper Alloy	—	—
④	Terminal	—	3	Copper Alloy	Plating silver	—
③	Housing	—	1	PBT	Black	—
②	Knob	—	1	PBT	Black	—
①	Cover	—	1	PBT	Black	—

APPROVALS
 DRAWN: JIANKUN.LIU 2015.5.26
 CHECKED: _____
 APPROVALS: _____
 TOLERANCES ARE: 30~0.15 ±0.20 ANGLE 10~20 ±0.25 UNIT: mm SCALE: 1:1
 5~10 ±0.20 ±2 DRAWING NO. _____
 SHENZHEN YUCHENG ELECTRONICS CO., LTD
 深圳市裕诚电子有限公司
 www.ycelectron.com
 M7-1122P
 PROD. SHEET 1 OF 1

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			