


NOTE:
 1.Rating:AC125V 5A/250V 3A
 2.Operating froce:25±10gf
 3.Mechanical Life:1,000,000
 3.Electrical Life:6000-10,000

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
8	Shrapnel 2	---	1	Copper Alloy	---	---
7	Shrapnel 1	---	1	Beryllium Copper	---	---
6	Contact	---	1	Copper Alloy	Plating silver	---
5	Lever	---	1	Stainless Steel	---	---
4	Terminal	---	3	Copper Alloy	Plating silver	---
3	Housing	---	1	PBT	Black	---
2	Knob	---	1	PBT	Black	---
1	Cover	---	1	PBT	Black	---



Circuit Diagram

APPROVALS		DATE		深圳市裕诚电子有限公司 SHENZHEN YUCHENG ELECTRONICS CO.,LTD	
DRAWN	J.X.Zhang	2014/8/20			
CHECKED				WEBSITE	www.ycelectron.com
APPROVALS				PART NO.	M7-1166P
TOLERANCES ARE		30~100	±0.30	ANGLE	UNIT: mm
		10~20	±0.25		SCALE: 1:1
		5~10	±0.20		PROJ:
		~ 5	±0.20		DRAWING NO.
					SHEET 1 OF 1

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			