



Recommended PCB Layout

### SPECIFICATIONS

- 1.RATING: DC30V 1.0A
- 2.MECHANICAL LIFE: 10,000 CYCLES.
- 3.PACKAGING: 1000PCS/REEL

③	Shell	—	1	Phosphor Bronze	Ni Plated	—
②	Contact	—	5	C2680R-H	Au Plated	—
①	Housing	—	1	LCP	Black	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS			DATE		<b>深圳市裕诚电子有限公司</b> SHENZHEN YUCHENG ELECTRONICS CO., LTD	
DRAWN	JIANKUN.LU	2015.5.29				
CHECKED			WEBSITE		www.ycelectron.com	
APPROVALS			PART NO.		MICRO-X673	
TOLERANCES ARE			30~80L: ±0.30	ANGLE	UNIT: mm	SCALE: 1:1
			10~30 ±0.25			
			5~10 ±0.20			
			~ 5 ±0.15			
			±2'	DRAWING NO.	SHEET 1 OF 1	

—	A	—	NEW	—	—	—
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.