



- NOTES :
- 1> Specification:
 - 1> Operating force: 1000gf Max
 - 2> Operating Temperature: -40° to +85°
 - 3> Storage Temperature: -40° to +85°
 - 4> Electrical life: 1000cycles 25mA 24VDC
 - 5> Mechanical Life: 3000cycles Operations
 2. PLATING:

GOLD FLASH 1u" (min.) SOLDER TAIL,
3u" GOLD PLATING ON THE CONTACT AREA,
WITH 50u" NICKEL UNDERPLATING OVERALL.
 3. PART NUMBER DESCRIPTION :
DSHP XX I S G E I

【包装方式: T=管装 R=Reel】
 【电鍍层: B=鍍触部 3u" 焊脚部 1.2u" G=鍍触部 3u" 焊脚部 3u" R=鍍触部 10u" 焊脚部 10u"】
 【G=鍍全金 S=内鍍金(接触部)外鍍锡(焊脚部)】
 【脚型: S脚 / J脚 / 埋脚 / A脚 / Z脚】
 【T=低推贴胶 S=低推不贴胶 L=长推】
 【产品P数: 02=2P 04=4P 06=6P 08=8P 10=10P 12=12P】

[Schematic]

【推进行程】



Number	Part Name	Material	Finished
①	Actuator	UL94 V0	White
②	Cover	UL94 V0	Black
③	Movable	Beryllium Copper	3u" Gold
④	Terminal	Brass	1u" Gold
⑤	Base	UL94 V0	Black
⑥	Terminal Contact	Brass	3u" Gold
⑦		UL94 V0	0.05mm Mylar

TOLERANCE UNLESS OTHERWISE SPECIFIED		ANGLES		PROJECTION	
UNER	ANGLES				
0 ± 0.25	0 ± 2'				
100 ± 0.15	0 ± 1'				
.000 ± 0.10	.00 ± 0.5'				
DESIGN		kathy		03/20/12	
DRAWING					
CHECK					
APPRO.					

深圳市裕诚电子有限公司
 SHEENZHEN YU CHENG ELECTRONICS CO., LTD
www.ycelectron.com
 M6-DF1. 27MM

FILE NO.: DSHP08TSGEET-A
 SIZE UNIT SCALE SHEET REV.
 A4 mm 2 : 1 TOP 1 A