



Circuit Diagram

PART NO.	
K2-1101SA	
K2-1101ST	
NO.1	
PART NO.	H
A	4.3
C	5

NO.2	
PART NO.	VIGOR
1	90 \pm 30
2	130 \pm 30
3	180 \pm 30
4	250 \pm 30
5	350 \pm 50

NO.3	
PART NO.	MATERIAL/QTY
S	SUS/1PC
D	SUS/2PCS

NO.4		
PART NO.	L	L1
A	8	10
B	8.5	11
C	9	11
D	9.5	12
E	10	12

NO.5-NO.6	
PART NO.	NOTE
01~99	SERIAL NUMBER

⑤	Terminal	—	2	Brass(0.30t)	Plating silver	—
④	Contact	—	1	F.Ag/SUS	Plating silver	—
③	Base	—	1	PA46	WHITE	—
②	Cover	—	1	SPCC	Plating Nickel	—
①	Keystoke	—	1	PA46	WHITE	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE	深圳市裕诚电子有限公司 SHENZHEN YUCHENG ELECTRONICS CO.,LTD				
DRAWN	J.X.Zhang	2013/5/30	WEBSITE	www.ycelectron.com			
CHECKED			PART NO.	M2-3922P			
APPROVALS			TOLERANCES ARE	30~90: ± 0.30	ANGLE	UNIT: mm	
				10~30: ± 0.20		SCALE: 1:1	
				5~10: ± 0.15	$\pm 2'$	PROJ:	
				~ 5: ± 0.10		DRAWING NO.	
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	SHEET 1 OF 1

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
—	A	—	NEW	—	—	—