



- Note:
1. Material:
    - 1.1 Housing: High temperature thermoplastic with g.f,UL94v-0
    - 1.2 Contact: copper alloy,t=0.15mm
    - 1.3 Shell: copper alloy,t=0.25mm
  2. Specification:
    - 2.1 Current rating:1.5PIN 1.8A Max/2,3,4PIN 1A Max.
    - 2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.
    - 2.3 Contact resistance: 30 mΩ Max.
    - 2.4 Insulation resistance: 100 MΩ Min.
    - 2.5 Total mating force: 3.57 Kgf Max.
    - 2.6 Total unmating force: 1.0 Kgf Min.
    - 2.7 Temperature range: -30°C~80°C

产品图 PRODUCT CHART DWG		深圳市裕诚电子有限公司 SHENZHEN YUCHENG ELECTRONICS CO., LTD								
公差一览表 TOLERANCE UNLESS OTHERWISE				单位 UNITS	MM	制图 DRAWING	陈雅	产品料号 PRODUCT PART NO.	MICRO-C07J	
X.	±0.30	X'	±5°	比例 SCALE	1:1	审核 CHKD	洪章波	产品名称 PRODUCT NO.	MICRO 5P母 (沉板式1.0) 四脚全插有边	
.X	±0.25	.X'	±2°							
.XX	±0.30	.XX'	±1°	日期 DATE	2016.2.5	核准 APPD	魏杰	角法 VIEW	版本 VER	A0
.XXX	±0.15	.XXX'	±0.5°							