



RECOMMENDED PCB LAYOUT

特性: Specifications:

电器: Electrical:

接触阻抗: Contact Resistance

50 milliohms MAX

耐电压: Dielectric Withstanding Voltage:

100 V AC AT Sea Level

绝缘阻抗: Insulation Resistance:

100 MEGA ohms MIN

材料: Material:

塑胶: Housing: High Temperature Thermoplastics,  
UL 94V-0 耐高温塑胶

端子: Contact: Copper Alloy 铜合金

铁壳: Shell: Copper Alloy 铜合金

电镀: Finish:

端子: Contact: Plated Gold in Mating Area;

Tin On Solder Tails

接触点镀金, 脚镀锡

铁壳: Shell:

Nickel/ Plating 镀镍

Ordering Informating

X - 5 - XX

X

Plastic Color

A=Black

Contact plating

01-Gold Flash

02-5u"Gold/ Tin

03-15u"Gold/ Tin

04-30u"Gold/Tin

尺寸未注公差参考±0.10



深圳市裕诚电子有限公司

SHENZHEN YUCHENG ELECTRONICS CO., LTD



成品图

品名	MINI USB B-TYPE 5P SMT 母座	MINI-92QT	单位	MM
设计	陈雅	www.ycelectron.com	比例	1:1
制图	洪章波	审核	魏杰	日期 2016.2.5