




- NOTES:
SPECIFICATION:
1. CURRENT RATING: 3A MAX
 2. VOLTAGE: 100 VAC
 3. TEMPERATURE RANGE: -30 °C ~ 85 °C
 4. CONTACT RESISTANCE: 40 MILLIONHM MAX
 5. INSULATION RESISTANCE: 100 MEGOHMS MIN.
 6. LNSERTION FORCE : 5N~20N
 7. UNMATING FORCE: 8N~20N
 8. DURABILITY: 10,000 CYCLES



RECOMMENDED PCB LAYOUT(TOP VIEW)

A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A3	SSTXN1	B10	SSRXN1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	SSRXN2	B3	SSTXN2
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME



<p>产品图 PRODUCT CHART DWG</p>		<p>深圳市裕诚电子有限公司 SHENZHEN YUCHENG ELECTRONICS CO., LTD</p>			
<p>公差一览表 TOLERANCE UNLESS OTHERWISE</p>		<p>单位 UNITS</p>	<p>制图 DRAWING</p>	<p>陈雅</p>	<p>产品料号 PRODUCT PART NO.</p>
X.	±0.30	X'	±5'	<p>审核 CHKD</p>	<p>洪章波</p>
.X	±0.25	.X'	±2'		
.XX	±0.30	.XX'	±1'	<p>日期 DATE</p>	<p>2016.2.5</p>
.XXX	±0.15	.XXX'	±0.5'		
		<p>比例 SCALE</p>	<p>1:1</p>	<p>核准 APPD</p>	<p>魏杰</p>
		<p>日期 DATE</p>	<p>2016.2.5</p>	<p>角法 VIEW</p>	<p>角法 VIEW</p>
				<p>TYPE-C-T24P</p>	<p>TYPE C母座板上前插后贴24P L=11.95</p>
				<p>版本 VER</p>	<p>A0</p>